



### PCB LAYOUT

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
03/26/05	B	4.39 [0.173] WAS 4.34 [0.171]	T.B.	B.S.	
1/07/06	C	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
2/25/06	D	LEAD FREE WAS Sn-Pb PLTD.	T.B.	B.S.	
03/09/12	E	REMOVED SOLDER TAILS FROM NOTE	T.B.	B.S.	
12/06/13	F	Updated Positive contact cross section view to mach part	T.B.	B.S.	



### NOTES:


#### MATERIAL:

HOLDER: PBT POLYESTER, BLACK, UL94V-0

POS. CONT.: PHOSPHOR BRONZE, SPRING TEMPER, NICKEL PLATED.

NEG. CONT.: PHOSPHOR BRONZE, SPRING TEMPER, NICKEL PLATED.

ROHS 2 COMPLIANT

Tolerance (Except as noted)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)			Scale Drawn By B.S.
Fractional ± .8 (.030)	Title COIN CELL HOLDER		Approved By T.B.
Angular ± 3°	Date 12/06/13	Drawing Number BH501	