


THRU HOLE




SPECIFICATIONS

Terminal: Brass, Tin Plate Screw: Steel, Zinc Plate Mounting Hole: .047 (1.2) Current Rating: 15 AMP

CAT. NO. 8730 (Screw Installed)

WIRE CONTACT



SPECIFICATIONS

Terminal: Brass, Tin Plate Screw: Steel, Zinc Plate

Contact: Phoshorus Bronze. Tin Plate Mounting Hole: .047 (1.2) **Current Rating: 15 AMP**

CAT. NO. 8737 (Screw Installed)

LOW PROFILE SCREW TERMINALS

These sturdy, low cost screw terminals, feature an anti-rotation tab for use with spade terminals. They are available with the screw installed and captivated, the screw unassembled or without a screw.


PRINCIPLE FEATURES

- · Easy to connect using solid or stranded wire, crimp lugs or terminals
- Anti-rotation tab for use with spade terminals
- · Supplied with screw installed and captivated, with screw unassembled, or without screw
- Stainless steel screw will not wick

Mounting Detail

∠.187 [4.7] DIA







6-32

SPECIFICATIONS Rated: 15 Amps

Terminal: .032 (.81) Brass, Matte Tin Plate Screw: Combination drive, Stainless Steel

CAT. NO. 1284 (No Screw Supplied)

CAT. NO. 1298 (Screw Supplied Unassembled)

CAT. NO. 1201 (Screw Installed & Captivated)

6-32 x .250 [6.3] L.

.187 [4.8]

SPECIFICATIONS


Rated: 15 Amps

Terminal: .064 (1.6) Brass, Matte Tin Plate

Screw: Brass, Nickel Plate

CAT. NO. 1205 (No Screw Supplied)

CAT. NO. 1207 (Screw Supplied Unassembled)



HEAVY DUTY SCREW TERMINALS - 30 AMP

These heavy duty terminals are available with the screw installed or unassembled, and feature easy access to connect solid or stranded wire, crimp type lugs or terminals.

PRINCIPLE FEATURES

- · Anti-rotation tab for use with spade terminals
- · Below the board notched leg, to facilitate mechanical and solder connections
- · Easy to connect using solid or stranded wire, crimp lugs or terminals
- Available with screw installed, unassembled, or without screw



10-32



SPECIFICATIONS Rated: 30 Amps

10-32

Terminal: .062 (1.6) Brass, Matte Tin Plate Screw: Combination drive, Stainless Steel

CAT. NO. 1293 (No Screw Supplied)

CAT. NO. 1299 (Screw Supplied Unassembled) CAT. NO. 1202 (Screw Installed & Captivated)


→ .406 [10.3]


437 [11.1]

156 [4.0]

.250 [6.4]

- .125 [3.2]






Brass, Matte Tin Plate Screw: Steel. Nickel Plate

CAT. NO. 1206 (No Screw Supplied) CAT. NO. 1208 (Screw Supplied Unassembled)

CAT. NO. 1283 (Screw Installed)



KEYSTONE

.187 [4.8]

.375 [9.6]