

► Cable Ties

► Cable Ties with Fasteners

► Cable Tie Tools

► Clamps and Clips

Heatshrink Moulded Shapes

► Mounts

► Heavy Duty Mounts

► Wire Connectors

▼ Wiring Duct

Solid Wall

Slotted Wall

High Density Slotted Wall

Covers

Accessories

► Wiring Protection

► Labels, Printers and Software

Pre-Terminated Networking

► Copper Network Solutions

► Fiber Network Solutions

► Jacks and Wall Plates

► Racks - Cable Management

► Surface Raceway Systems

PR1M4

Panel Rivet, PA66, Natural, 1000/pkg

Article Number: 181-00139

Part Number: PR1M4

Type: PR1

►Find a Distributor

►Order Samples

►Get Technical Drawings

Share

►Base Data

Part No.	PR1M4
Type	PR1
Color	Natural (NA)
Features	- Nylon material holds duct securely to panel - Non-metallic rivet will not corrode; ensuring longevity
Application Method	The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. A panel rivet tool is also available for quick and easy installation of the drive rivets.
Typical Application	The panel thickness (including the duct thickness) should be a maximum of 3/16".

►Product Dimensions

Min. Tensile Strength	478N
Max. Panel Thickness	7.00mm
Min. Panel Thickness	3.90mm
Mounting Hole Ø	5.0mm
Max. Ø	0.51mm

►Material and Specifications

Material	Polyamide 6.6 (PA66)
Flammability	UL94 V2
Material Specification	RoHS
Operating Temperature	-40 °F to +176 °F (-40 °C to +80 °C)
ROHS Conformity	RoHS
Specification	IMQ

►Logistic and Packaging

Packaging Type	bag
Pkg. Qty.	1000 / 1000
Carton Qty.	1000
UPC	089306239109

Find a Distributor

Get Product Samples

Get Technical Drawings

http://www.hellermannntyton.us/productDetail.aspx?lon=PR1M4&ref=search.aspx[11/8/2013 11:41:45 AM]