- Cable Ties
- Cable Ties with Fasteners
- Cable Tie Tools
- Clamps and Clips
- Heatshrink Moulded Shapes
- Mounts
- Heavy Duty Mounts
- Wire Connectors
- Wiring Duct
- Wiring Protection
- Labels, Printers and Software
  - Nameplate Systems
    - **Solar Installation Labels**
    - Foam Nameplate Labels
    - Plastic Nameplate Markers
    - Continuous Vinyl Labels
    - Metalized Labels
    - Q Tags
  - Automatic Label Applicator
  - Portable Printer
  - Portable Printer Labels
  - Portable Printer Accessories
  - Thermal Transfer Printers
  - Thermal Transfer Labels
  - Thermal Printer Accessories
  - TagPrint Software
  - Heat Shrinkable Labels
  - Laser Tag Labels
  - Ink Jet Labels
  - Dot Matrix Labels
  - Hand Writable Labels
  - Pre-Printed Wire Labels
  - Plastic Wire Markers
  - Specialty Labels
- Pre-Terminated Networking
- Copper Network Solutions
- Fiber Network Solutions
- Jacks and Wall Plates
- Racks - Cable Management
- Surface Raceway Systems

596-00326

Pre-Printed Solar Label, 3.75" X 2", BIPOLAR SOLAR ARRAY, Red, 50/pkg

Article Number: 596-00326
Part Number: 596-00326
Type: BIPOLARPV

Find a Distributor
Order Samples
Get Technical Drawings
Share

Base Data

Part No.	596-00326
Type	BIPOLARPV
Color	Red (RD)
Features	• Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life. • Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection. • Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes. • The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.
Application Method	Labels are applied by hand to PV installations where durable UV resistant marking is required.
Color of Print	White (WH)
Technical Description	3.75" X 2" White text on red background that reads as: "WARNING - BIPOLAR PHOTOVOLTAIC ARRAY. DISCONNECTION OF NEUTRAL OR GROUNDED CONDUCTORS MAY RESULT IN OVERVOLTAGE ON ARRAY OR INVERTER." - 50 per roll.
Typical Application	This label would be used on a bipolar array (usually larger solar farms) All DC equipment would require this label.

Product Dimensions

Width (W) (imperial)	3.75"
Width (W)	92.25mm
Height (H)	2.0" / 50.8mm

Material and Specifications

Material	Vinyl
Adhesive	Acrylic / Acryl
Adhesive Operating Temperature	-40 °F to +174 °F (-40 °C to +79 °C)
Halogenfree	YES
Material Specification	HF

Operating Temperature	-40 °F to +174 °F (-40 °C to +79 °C)
ROHS Conformity	RoHS
UL Recognized (US and Canada)	Yes

Logistic and Packaging

Packaging Type	roll
Pkg. Qty.	50 / 50

Find a Distributor | Get Product Samples | Get Technical Drawings

© HellermannTyton North America 2011 | TS16949, ISO 9001 and ISO 14001 Certified
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512