



# Eco-Surge 12-Outlet Home/Business Theater Surge Protector, 10-ft. Cord, 3600 Joules - Accommodates 4 Transformers

# MODEL NUMBER: AV1210SATG





# **Description**

Tripp Lite's AV1210SATG offers reliable, GREEN surge technology that protects your A/V installations, the environment and your wallet. This ECO-SURGE offers a unique Netbook switch that allows users to select wattage, so ECO-SURGE are the only green surge suppressors compatible with all PCs, Notebooks and Netbooks. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. The TLP1210SATG offers 3600 joules of advanced surge protection for all A/V components. You can see and hear the difference: sharper, crisper video; deeper, fuller audio; longer component life spans. Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 12 outlets (with transformer spacing and sliding safety covers), 2-line 2.2GHz gold coaxial protection and 1-line tel/modem/Ethernet (100BaseT, high-speed) protection safeguard an entire home/business theater system. Includes two diagnostic LEDs and four status LED indicators, color-coordinated holographic outlet/plug labels, 10-ft. cord with a right-angle plug, 6-ft. gold coaxial cable and 6-ft. network cable. \$250,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

#### **Features**

- Green Outlet Array; "Master" outlet controls power flow for 1 primary and up to 8 peripheral
  components. "Power Save" outlets cut AC power to 8 connected components when not in use perfect
  for non-essential components that do not save settings like DVD players, gaming consoles, amplifiers
  and speaker systems. "Always On" outlets provide continuous power to 3 critical devices that save
  settings like DVRs and recorders (TiVo), cable and satellite boxes
- User-adjustable wattage control switch allows for high-wattage (over 25W) and low-wattage (over 15W) components to serve as Master device
- Auto/Manual Switch allows users to switch between GREEN (auto) power-save mode and standard (manual) surge protection
- 3600 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 12 widely spaced surge-protected NEMA 5-15R AC outlets safeguard and entire home/business theater system while accommodating up to 4 large transformers

# **Highlights**

- Auto/manual switch offers GREEN energy-savings or standard protection
- Unique Netbook Switch allows user to select wattage
- 12 outlets / 10-ft cord; 3600 joule rating
- 2-line 2.2GHz digital gold coax connectors
- 1-line tel/modem/network (100BaseT, high-speed) surge protection

### **Package Includes**

- AV1210SATG ECO-SURGE Home/Business Theater Surge Suppressor
- 6-ft gold coax cable
- · 6-ft network cable
- Instruction manual with warranty information





- Sliding safety covers protect against accidental contact
- 2 sets of surge-protected 2.2GHz gold coaxial connectors safeguard components on cable, satellite and antenna line
- 1-line tel/modem/Ethernet (100BaseT, high-speed) surge protection safeguards personal video recorders (PVRs) on a single dial-up or Ethernet line. Built-in splitter (1 jack in and 2 jacks out) allows simultaneous connection of two devices sharing a single line
- 10-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 2 diagnostic LEDs alert user to protection and grounded status and 4 status LEDs indicates when AC power is present
- Keyhole slots provide convenient wall or cabinet mounting
- RoHS Compliant

# **Specifications**

OVERVIEW		
UPC Code	037332155597	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	228000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	10	
Right-Angle Plug	Yes	
Input Cord Length (m)	3.05	
Integrated Cord Clip	No	
ОИТРИТ		
Output Capacity (VA)	15	
Output Capacity (Watts)	1800	
Frequency Compatibility	60 Hz	
Output Receptacles	(12) 5-15R	
Transformer Accommodation	(8) Yes	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	





SURGE / NOISE SUPPRESSION  AC Suppression Joule Rating 3600  AC Suppression Response Time < 1 ns  Protection Modes Includes full normal mode (H-N) and common mode (N-G  UL1449 Let Through Rating 330, 400, 400  EMI / RFI Filtering Up to 40 dB  Automatic Shut-Off Yes  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection Details 1 line  Cable (Coax) Protection Yes  Cable (Coax) Protection Details 2 line  Network (Ethernet) Protection Yes  Telephone/DSL Protection Yes  PHYSICAL  Color Black  Material of Construction Plastic  Power Cord Color Black  Housing Color Dark Gray  Mounting Holes or Slots Yes  Slot or Hole Mount Measurement (Center to Center) Distance between horizontal tabs = 152mm; Distance between Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80	/ H-G) line surge suppression	
AC Suppression Response Time	/ H-G) line surge suppression	
Protection Modes  UL1449 Let Through Rating  330, 400, 400  EMI / RFI Filtering  Up to 40 dB  Automatic Shut-Off  Yes  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection Details  Cable (Coax) Protection Details  2 line  Network (Ethernet) Protection  Yes  PHYSICAL  Color  Black  Material of Construction  Plastic  Power Cord Color  Black  Housing Color  Mounting Holes or Slots  Siot or Hole Mount Measurement (Center to Center)  Cutlets Measurement (Center to Center)  Receptacle Color  Shipping Dimensions (hwd / in.)  I up to 40 dB  Automatic (H-N) and common mode (N-G  330, 400, 400  Black  I line  Ves  2 line  Pes  Physical  Plastic  Power Cord Color  Black  Distance between horizontal tabs = 152mm; Distance between to center)  Distance between standard outlets = 25.4mm; Distance between Shipping Dimensions (hwd / in.)  13.60 x 2.00 x 8.80	/ H-G) line surge suppression	
UL1449 Let Through Rating  330, 400, 400  EMI / RFI Filtering  Qu to 40 dB  Automatic Shut-Off  Yes  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection Details  Cable (Coax) Protection  Yes  Cable (Coax) Protection Details  2 line  Network (Ethernet) Protection  Yes  PHYSICAL  Color  Black  Material of Construction  Plastic  Power Cord Color  Black  Housing Color  Dark Gray  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Outlets Measurement (Center to Center)  Receptacle Color  Shipping Dimensions (hwd / in.)  13.60 x 2.00 x 8.80	/ H-G) line surge suppression	
EMI / RFI Filtering  Automatic Shut-Off  Yes  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection Details  Cable (Coax) Protection Details  2 line  Network (Ethernet) Protection  Yes  Telephone/DSL Protection  Yes  PHYSICAL  Color  Black  Material of Construction  Power Cord Color  Black  Housing Color  Dark Gray  Mounting Holes or Slots  Yes  Slot or Hole Mount Measurement (Center to Center)  Outlets Measurement (Center to Center)  Receptacle Color  Shipping Dimensions (hwd / in.)  1 line  Yes  1 line  A line  Yes  Physical  Pass  A line  Pes  A line  A line  A line  Yes  Black  Distance between horizontal tabs = 152mm; Distance between to Center)  Distance between standard outlets = 25.4mm; Distance between to Center)  Receptacle Color  Gray; green  Shipping Dimensions (hwd / in.)		
Automatic Shut-Off  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection Details 1 line  Cable (Coax) Protection Details 2 line  Network (Ethernet) Protection Yes  Telephone/DSL Protection Yes  PHYSICAL  Color Black  Material of Construction Plastic  Power Cord Color Black  Housing Color Dark Gray  Mounting Holes or Slots Yes  Slot or Hole Mount Measurement (Center to Center)  Outlets Measurement (Center to Center)  Receptacle Color Gray; green  Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80		
Telephone/DSL Protection Details 1 line  Cable (Coax) Protection Protection Yes  Cable (Coax) Protection Details 2 line  Network (Ethernet) Protection Yes  Telephone/DSL Protection Yes  PHYSICAL  Color Black  Material of Construction Plastic  Power Cord Color Black  Housing Color Dark Gray  Mounting Holes or Slots Yes  Slot or Hole Mount Measurement (Center to Center) Distance between horizontal tabs = 152mm; Distance between Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80		
Telephone/DSL Protection Details  Cable (Coax) Protection  Yes  Cable (Coax) Protection Details  2 line  Network (Ethernet) Protection  Yes  Telephone/DSL Protection  Yes  PHYSICAL  Color  Black  Material of Construction  Plastic  Power Cord Color  Black  Housing Color  Dark Gray  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Outlets Measurement (Center to Center)  Receptacle Color  Shipping Dimensions (hwd / in.)  1 line  1 line  Yes  2 line  Nes  2 line  Nes  1 line  2 line  Yes  Distance between standard outlets = 25.4mm; Distance between standard outlets		
Cable (Coax) Protection  Yes  Cable (Coax) Protection Details  2 line  Network (Ethernet) Protection  Yes  Telephone/DSL Protection  Yes  PHYSICAL  Color  Black  Material of Construction  Plastic  Power Cord Color  Black  Housing Color  Dark Gray  Mounting Holes or Slots  Yes  Slot or Hole Mount Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between Center)  Outlets Measurement (Center to Center)  Distance between standard outlets = 25.4mm; Distance between Shipping Dimensions (hwd / in.)  13.60 x 2.00 x 8.80		
Cable (Coax) Protection Details  Network (Ethernet) Protection  Yes  Telephone/DSL Protection  PHYSICAL  Color  Black  Material of Construction  Power Cord Color  Housing Color  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Outlets Measurement (Center to Center)  Receptacle Color  Shipping Dimensions (hwd / in.)  Yes  Yes  2 line  Yes  Black  Distance between horizontal tabs = 152mm; Distance between to Center of		
Network (Ethernet) Protection  Yes  Telephone/DSL Protection  Yes  PHYSICAL  Color  Black  Material of Construction  Plastic  Power Cord Color  Black  Housing Color  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Outlets Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between horizontal counters and and outlets = 25.4mm; Distance between Shipping Dimensions (hwd / in.)  13.60 x 2.00 x 8.80		
Telephone/DSL Protection  PHYSICAL  Color  Black  Material of Construction  Plastic  Power Cord Color  Black  Housing Color  Dark Gray  Mounting Holes or Slots  Slot or Hole Mount Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between to Center)  Distance between standard outlets = 25.4mm; Distance between to Center)  Receptacle Color  Gray; green  Shipping Dimensions (hwd / in.)		
PHYSICAL  Color Black  Material of Construction Plastic  Power Cord Color Black  Housing Color Dark Gray  Mounting Holes or Slots Yes  Slot or Hole Mount Measurement (Center to Center) Distance between horizontal tabs = 152mm; Distance between to Center)  Outlets Measurement (Center to Center) Distance between standard outlets = 25.4mm; Distance between to Center)  Receptacle Color Gray; green  Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80		
Color Black  Material of Construction Plastic  Power Cord Color Black  Housing Color Dark Gray  Mounting Holes or Slots Yes  Slot or Hole Mount Measurement (Center to Center) Distance between horizontal tabs = 152mm; Distance between to Center)  Outlets Measurement (Center to Center) Distance between standard outlets = 25.4mm; Distance between Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80		
Color Black  Material of Construction Plastic  Power Cord Color Black  Housing Color Dark Gray  Mounting Holes or Slots Yes  Slot or Hole Mount Measurement (Center to Center) Distance between horizontal tabs = 152mm; Distance between to Center)  Outlets Measurement (Center to Center) Distance between standard outlets = 25.4mm; Distance between Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80		
Power Cord Color  Housing Color  Dark Gray  Mounting Holes or Slots  Yes  Slot or Hole Mount Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between to Center)  Distance between standard outlets = 25.4mm; Distance between to Center)  Receptacle Color  Gray; green  Shipping Dimensions (hwd / in.)  13.60 x 2.00 x 8.80		
Housing Color  Dark Gray  Mounting Holes or Slots  Yes  Slot or Hole Mount Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between to Center)  Distance between standard outlets = 25.4mm; Distance between to Center)  Receptacle Color  Gray; green  Shipping Dimensions (hwd / in.)  Dark Gray  Yes  Distance between standard outlets = 25.4mm; Distance between to Center)  13.60 x 2.00 x 8.80		
Mounting Holes or Slots  Yes  Slot or Hole Mount Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between to Center to Center to Center to Center (Center to Center)  Distance between standard outlets = 25.4mm; Distance between tender of Center (Center)  Receptacle Color  Gray; green  Shipping Dimensions (hwd / in.)  13.60 x 2.00 x 8.80		
Slot or Hole Mount Measurement (Center to Center)  Distance between horizontal tabs = 152mm; Distance between to Center to Center to Center to Center to Center to Center)  Distance between standard outlets = 25.4mm; Distance between standard outlets = 25.4mm; Distance between to Center		
(Center to Center)       Distance between nonzontal tabs = 152mm; Distance between centers         Outlets Measurement (Center to Center)       Distance between standard outlets = 25.4mm; Distance between centers         Receptacle Color       Gray; green         Shipping Dimensions (hwd / in.)       13.60 x 2.00 x 8.80		
Receptacle Color  Shipping Dimensions (hwd / in.)  Gray; green  13.60 x 2.00 x 8.80	veen vertical tabs = 73.5mm	
Shipping Dimensions (hwd / in.) 13.60 x 2.00 x 8.80	etween transformer outlets = 57mm	
Shipping Dimensions (hwd / cm) 34.54 x 5.08 x 22.35		
Shipping Weight (lbs.) 3.30		
Shipping Weight (kg) 1.50		
Unit Dimensions (hwd / in.) 1.510 x 4.660 x 12.410		
Unit Dimensions (hwd / cm) 3.84 x 11.84 x 31.52		
Unit Weight (lbs.) 2.56		
Unit Weight (kg) 1.16		
FEATURES & SPECIFICATIONS		
Green Energy-Saving Features Power saving auto-shutoff ECO outlets		
Rotatable Outlets No		





Antimicrobial	No	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.