

# Internet Office 500VA Low-profile Standby 120V UPS

MODEL NUMBER: **TM500**



## Highlights

- 6 outlets (3 UPS/surge, 3 surge-only)
- Built-in RJ11 jacks provide complete modem/fax surge protection
- Under-monitor design supports virtually any monitor
- \$150,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

## Package Includes

- TM500 UPS System
- 6-ft. telephone cord
- Warranty information
- Instruction manual

## Description

Tripp Lite's space-saving TM500 Under-Monitor UPS System provides complete power protection for your entire computer set-up, even power hungry peripherals. 500 VA of battery backup maintains your Internet connection, allowing you to work online through short blackouts or safely shut down during longer ones. Unique design features 6 outlets (3 UPS & surge + 3 surge-only), individually switched outlets and diagnostic LEDs. Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment. A 6-ft. telephone cord is also included. \$150,000 Ultimate Lifetime Insurance (USA, Puerto Rico, & Canada Only).

## Features

- 500 VA output power rating (300 watts)
- Up to 30 minutes typical backup time
- 6 protected outlets (3 UPS & surge + 3 surge-only); 6 ft. cord
- Unique space-saving, under-monitor console design
- Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment; 6 ft. telephone cord included
- Complete surge protection and EMI/RFI noise filtering
- \$150,000 Ultimate Lifetime Insurance (USA, Puerto Rico. & Canada Only) —
- Master switch and 4 auxiliary switches give you control over multiple pieces of your equipment
- 4 diagnostic LEDs indicate AC Present, line fault, On Battery & Battery Low/Replace

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332033154 |
| UPS Type | Standby      |
| INPUT    |              |

|   |  |
|---|--|
| Input Phase                                     | Single-Phase   |
| Rated input current (Maximum Load)              | 15A  |
| Nominal Input Voltage(s) Supported              | 120V AC  |
| UPS Input Connection Type                       | 5-15P  |
| UPS Input Cord Length (ft.)                     | 6  |
| UPS Input Cord Length (m)                       | 1.8  |
| Recommended Electrical Service                  | 15A 120V   |
| <b>OUTPUT</b>                                   |  |
| Output Capacity (VA)                            | 500  |
| Output Capacity (Watts)                         | 300  |
| Frequency Compatibility                         | 60 Hz  |
| Output Voltage Regulation (Battery Mode)        | +/- 5%   |
| UPS Output Receptacles (Surge Suppression Only) | 3 UPS outlets, 3 surge-only outlets  |
| Output AC Waveform (AC Mode)                    | Sine wave  |
| Output AC Waveform (Battery Mode)               | PWM sine wave  |
| Nominal Output Voltage(s) Supported             | 120V   |
| Output Receptacles                              | (6) 5-15R  |
| <b>BATTERY</b>                                  |  |
| Runtime Full Load (min.)                        | 6 min. (300w)  |
| Runtime Half Load (min.)                        | 17 min. (150w)   |
| Expandable Runtime                              | No   |
| DC System Voltage (VDC)                         | 12   |
| Battery Recharge Rate (Included Batteries)      | Less than 4 hours from 10% to 90%  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>    |  |
| Switches  | 2 Switches control off/on power status and alarm-cancel/self-test operation, plus 4 switches control individual output receptacles |
| Audible Alarm                                   | Audible alarm indicates power-failure  |
| LED Indicators                                  | Front panel LEDs indicate line power status, battery power status and battery low/replace status                                   |
| <b>SURGE / NOISE SUPPRESSION</b>                |  |
| UPS AC Suppression Joule Rating                 | 480  |
| UPS AC Suppression Response Time                | Instantaneous  |



Powering Business Worldwide



|   |  |
|---|--|
| UPS Dataline Suppression                                      | 1 line TEL/DSL (1 in / 1 out)                              |
| EMI / RFI AC Noise Suppression                                | Yes  |
| <b>PHYSICAL</b>   |  |
| Primary Form Factor   | Desktop  |
| Installation Form Factors Supported with Included Accessories | Under-monitor console                                      |
| Primary UPS Depth (mm)  | 318  |
| Primary UPS Height (mm)                                       | 51   |
| Primary UPS Width (mm)  | 343  |
| Shipping Dimensions (hwd / in.)                               | 16.00 x 15.00 x 4.00                                       |
| Shipping Dimensions (hwd / cm)                                | 40.64 x 38.10 x 10.16                                      |
| Shipping Weight (lbs.)  | 12.00  |
| Shipping Weight (kg)  | 5.44   |
| UPS Housing Material  | PVC  |
| UPS Power Module Dimensions (hwd, cm)                         | 5.08 x 34.29 x 31.75                                       |
| UPS Power Module Dimensions (hwd, in.)                        | 2 x 13.5 x 12.5  |
| UPS Power Module Weight (kg)                                  | 5.31   |
| UPS Power Module Weight (lbs.)                                | 11.7   |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius  |
| Storage Temperature Range                                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity   | 0 to 95%, non-condensing                                   |
| AC Mode BTU / Hr. (Full Load)                                 | 65.1   |
| AC Mode Efficiency Rating (100% Load)                         | 94%  |
| Battery Mode Heat Dissipation (BTU/Hr) @ Full Load            | 88.7   |
| <b>COMMUNICATIONS</b>   |  |
| Communications Interface                                      | None   |
| <b>LINE / BATTERY TRANSFER</b>                                |  |
| Transfer Time   | 2-4 milliseconds   |
| Low Voltage Transfer to Battery Power (Setpoint)              | 101  |
| <b>FEATURES &amp; SPECIFICATIONS</b>                          |  |



Powering Business Worldwide



|   |  |
|---|--|
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported   |
| <b>WARRANTY &amp; SUPPORT</b>                               |  |
| Product Warranty Period (Worldwide)                         | 2-year limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$150,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

1000 Eaton Boulevard  
 Cleveland, OH 44122  
 United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
 Eaton is a registered trademark. All other trademarks  
 are the property of their respective owners.