

Product SKU: C1360.21.90

Product Description: Speaker Wire, UL Listed (Wires, Misc.) 120V max., No. of Conductors: 2, Gauge Size (AWG): 20, Conductor/Strands: 10/30, Jacket: Premium Grade PVC - Clear - 1000 Ft. Spool

Product Category: Electronics - Special Applications - Audio, Video, and Entertainment Cable - Speaker Wire - Clear



Product Construction:

- | | |
|--------------------|--|
| Conductor: | <ul style="list-style-type: none">• 24 thru 12 AWG fully-annealed 1 bare, 1 tin stranded copper per ASTM B-174 |
| Insulation/Jacket: | <ul style="list-style-type: none">• Premium grade PVC |

Product Specification:

- | | |
|------------------------------------|---|
| No. of Conductors: | <ul style="list-style-type: none">• 2 |
| Conductor Size (AWG): | <ul style="list-style-type: none">• 20 |
| Conductor/Strands: | <ul style="list-style-type: none">• 10/30 |
| Jacket Color: | <ul style="list-style-type: none">• Clear |
| Nominal Insulation Thickness (in): | <ul style="list-style-type: none">• 0.020 |
| Nominal Insulation Thickness (mm): | <ul style="list-style-type: none">• 0.51 |
| Nominal Outside Diameter (in): | <ul style="list-style-type: none">• 0.085 x 0.160 |
| Nominal Outside Diameter (mm): | <ul style="list-style-type: none">• 2.16 x 4.06 |
| Standard Packaging: | <ul style="list-style-type: none">• 1000' Spool |
| Standard Package Quantity: | <ul style="list-style-type: none">• 2 |
| UPC #: | <ul style="list-style-type: none">• 079407762385 |

| | |
|-----------------------------|--|
| Put-up: | <ul style="list-style-type: none"> • 1000 |
| SCC-14: | <ul style="list-style-type: none"> • 50079407762388 |
| Cube: | <ul style="list-style-type: none"> • 1330.89 |
| Weight Per Unit of Measure: | <ul style="list-style-type: none"> • .01 |
| ColorOption: | <ul style="list-style-type: none"> • Clear |

Product Information:

| | |
|---------------|--|
| Applications: | <ul style="list-style-type: none"> • Hi-fi and stereo speaker wire • Juke boxes • Lamps • Radios • Suggested voltage rating: 120 Volts • Not for in-wall use |
| Compliances: | <ul style="list-style-type: none"> • UL Wires Misc. (UL: 120V) |
| Packaging: | <ul style="list-style-type: none"> • 1000' (305 m) Spools • 500' (152 m) Spools • Other put-ups available- consult Customer Service |

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**