

151-00978

High Torque Axial Mount, Bolt Hole Dia .405 in, PA66HIRHS, Black, 500/pkg

Article Number: 151-00978

Part Number: 151-00978

Type: SAM400B



[Find a Distributor](#)

[Order Samples](#)


[Get Technical Drawings](#)

[!\[\]\(56549452e01ca28bdf2500ced9653143_img.jpg\) \[!\\[\\]\\(235f8f87c36d896db1ddff2848125c86_img.jpg\\) \\[!\\\[\\\]\\\(4c4afa2dcab95991c60f31fce713d641_img.jpg\\\) \\\[!\\\\[\\\\]\\\\(1205f6f8a2eee5164f325ab7908828d5_img.jpg\\\\) | \\\\[!\\\\\[\\\\\]\\\\\(5649178bcab2dc69cdc8b143e41f5574_img.jpg\\\\\) Share\\\\]\\\\(#\\\\)\\\]\\\(#\\\)\\]\\(#\\)\]\(#\)](#)

[Base Data](#)

Part No.	151-00978
Type	SAM400B
Color	Black (BK)
Features	• Positions bundles off cross members and frame rails to prevent abrasion and chafing. • Metal insert bushing accommodates high torque installation. • Made with high impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.
Typical Application	High Torque Axial Mounts position bundles in the center of frame rails and cross members to prevent rubbing and chafing against hole edges. These mounts contain a metal bushing on the inside to accommodate high torque installation with high impact wrenches.

[Product Dimensions](#)



Length (L)	1.2" / 29.9mm
Width (W) (imperial)	1.0"
Width (W)	24.3mm
Width (W2)	1.8" / 45.7mm
Height (H)	1.8" / 44.9mm
Max. Ø Bundle	2.0" / 50.8mm
Mounting Hole Ø	0.405" / 10.29mm

[Material and Specifications](#)

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
----------	--

- ▶ [Cable Ties](#)
- ▶ [Cable Ties with Fasteners](#)
- ▶ [Cable Tie Tools](#)
- ▶ [Clamps and Clips](#)
- ▶ [Heatshrink Moulded Shapes](#)
- ▶ [Mounts](#)
- ▼ [Heavy Duty Mounts](#)
 - [Axial Oval Mounts](#)
 - [Cable Guide Standoff](#)
 - [Fir Tree Mounts](#)
 - [H-Mounts](#)
 - [HC Clamps](#)
 - [High Torque Mounts](#)
 - [Medium Torque Mounts](#)
 - [Standard Torque Mounts](#)
 - [Saddle Mounts](#)
 - [Mounting Cradle](#)
 - [Weld Stud Mounts](#)
- ▶ [Wire Connectors](#)
- ▶ [Wiring Duct](#)
- ▶ [Wiring Protection](#)
- ▶ [Labels, Printers and Software](#)
 - [Pre-Terminated Networking](#)
- ▶ [Copper Network Solutions](#)
- ▶ [Fiber Network Solutions](#)
- ▶ [Jacks and Wall Plates](#)
- ▶ [Racks - Cable Management](#)
- ▶ [Surface Raceway Systems](#)

Flammability	UL94 HB
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
 Logistic and Packaging	
Packaging Type	bag
Pkg. Qty.	500
EAN code	4031026446790
UPC	089306339984

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)