



## T50MR0HSM4

Screw Mount Tie, 50 lbs. 8.5" Max Bundle Diameter 1.8", #10 Screw, PA66, Natural, 1,000/pkg

Article Number: 113-05013

Part Number: T50MR0HSM4

Type: T50MR

### Base Data

|                                      |                                                                                                                                                                                   |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Part No.</b>                      | T50MR0HSM4                                                                                                                                                                        |
| <b>Type</b>                          | T50MR                                                                                                                                                                             |
| <b>Color</b>                         | Black (BK)                                                                                                                                                                        |
| <b>Features</b>                      | <ul style="list-style-type: none"> <li>• Mount design secures firmly with any #10 Screw.</li> <li>• Screw mount style creates low insertion and high extraction force.</li> </ul> |
| <b>Identification Plate Position</b> | none                                                                                                                                                                              |
| <b>Releasable Closure (Yes/No)</b>   | No                                                                                                                                                                                |
| <b>Tie Closure</b>                   | plastic pawl                                                                                                                                                                      |
| <b>Typical Application</b>           | The 'T' range of cable ties have a built in mounting hole and once fastened around the cables the bundle can be simply secured to the panel with a screw or bolt.                 |
| <b>Variant</b>                       | Inside Serrated                                                                                                                                                                   |

### Product Dimensions

|                              |                |
|------------------------------|----------------|
| <b>Min. Tensile Strength</b> | 50.0lbs / 225N |
| <b>Length (L)</b>            | 8.5" / 215.0mm |
| <b>Width (W) (imperial)</b>  | 0.18"          |
| <b>Width (W)</b>             | 4.7mm          |
| <b>Height (H)</b>            | 0.22" / 5.5mm  |
| <b>Min. Ø Bundle</b>         | 0.06" / 1.5mm  |
| <b>Max. Ø Bundle</b>         | 1.8" / 45.0mm  |
| <b>Mounting Hole Ø</b>       | 0.21" / 5.4mm  |
| <b>Thickness</b>             | 1.2mm          |

## Material and Specifications

---

|                                      |                                                                                        |
|--------------------------------------|----------------------------------------------------------------------------------------|
| <b>Material</b>                      | Polyamide 6.6 heat stabilized (PA66HS) / Polyamide 6.6 (PA66)                          |
| <b>CSA Certified</b>                 | No                                                                                     |
| <b>Flammability</b>                  | UL94 V2                                                                                |
| <b>Material Specification</b>        | RoHS                                                                                   |
| <b>Operating Temperature</b>         | -40 °C to +105 °C / -40 °F to +221 °F (-40 °C to +105 °C)                              |
| <b>ROHS Conformity</b>               |  RoHS |
| <b>Specification</b>                 | UL                                                                                     |
| <b>UL Listed (US and Canada)</b>     | No                                                                                     |
| <b>UL Recognized (US and Canada)</b> | Yes                                                                                    |

## Logistic and Packaging

---

|                       |               |
|-----------------------|---------------|
| <b>Packaging Type</b> | bag           |
| <b>Pkg. Qty.</b>      | 1000          |
| <b>Carton Qty.</b>    | 5000          |
| <b>EAN code</b>       | 4031026418438 |
| <b>UPC</b>            | 089306085881  |