



www.hellermanntyton.co.uk | Products | Cable Ties and Fixings | Fixing Ties

2-Piece Fixing Ties with Fir Tree, with Disc T50SFT5



Fir Tree Parts FT5, Article number: 150-55943

- Pre-assembled 2-piece fixing tie with fir tree foot part
- Cable tie head can be moved after bundling
- Easy to assemble without the need for a tool
- Disc adjusts tie for pressure from various directions and minimises access of dust, dirt and water
- Fir tree foot part can be used for a variety of panel thicknesses
- Suitable for use within threaded holes

Primarily designed for fixing cable harnesses in the automotive industry their simplicity, and ease of use, has seen these parts used in everything from aircraft, to switch-gear, to washing machines.



Print

Base Data

Application Tool	MK20, MK3PNSP2, MK3SP, MK7P, MK7, MK7HT
Colour	Black (BK), Grey (GY)
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Product Family	Fir Tree Parts FT5
Product Group	2-Piece Fixing Ties with Fir Tree, with Disc
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T50SFT5-MC1-BKGY-D1
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	34.0 mm
Bundle Ø max. (imperial)	1.4 "
Bundle Ø min.	4.0 mm
Bundle Ø min. (imperial)	0.06 "
Disc Ø	16.0 mm
Disc Ø (imperial)	0.63 "
Fixing Hole Diameter D (Imperial)	0.18 - 0.2 "
Height (H)	1.2 mm
Height (H) (imperial)	0.05 "
Height (H2)	6.9 mm
Height (H2) (imperial)	0.27 "
Hole Ø	5 mm
Hole Ø (FH)	4.5 - 5.0 mm
Hole Ø (FH) min.	4.5 mm
Length (L)	150 mm
Length (L) (imperial)	6 "
Length (L2)	11.6 mm
Length (L2) (imperial)	0.46 "
Length (L3) (imperial)	0.54 "
Min. Tensile Strength (lbs)	50 lbs
Min.Tensile Strength (N)	225 N
Panel Thickness max.	3 mm
Panel Thickness max. (imperial)	0.12 "
Panel Thickness min.	0.7 mm
Panel Thickness min. (imperial)	0.03 "

Thickness (T)	1.2 mm
Width (W)	4.6 mm
Width (W) (imperial)	0.18 "
Width (W2)	9 mm
Width (W2) (imperial)	0.35 "
Width (W3) (imperial)	0.2 "

Logisitic and Packaging

Carton Quantity	5000 pcs.
EAN code	4031026121482
Pack Cont.	500
Quantity of Europallet	60000 pcs.
Quantity per	Bag
UPC	089306271369
Weight	2.3 kg

Material and Specifications

Cable Tie	Polyamide 6.6 Heat Stabilised (PA66HS)
Flammability	UL94 V2
Foot Part	Polyamide 6.6 (PA66)
Material	Polyamide 6.6 Heat Stabilised (PA66HS), Polyamide 6.6 (PA66)
Material	PA66HS, PA66
Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)
Operating Temperature Foot Part (Metric)	-40 °C to +85 °C, (+105 °C, 500 h)

More Information

UNSPSC Key	39121717
------------	----------