

Home

Events

Careers

How To Buy

Contact

HellermannTyton

Products

Industries

Resources

News

About Us

▶ Cable Ties

▼ Cable Ties with Fasteners

▶ Arrowhead Push Mount Ties

▶ Button Head Cable Ties

▶ Edge Clip Cable Ties

▶ Fir Tree Mount Cable Ties

▶ Screw Mount Cable Ties

▶ Stud Mount Cable Ties

▶ Cable Tie Tools

▶ Clamps and Clips

▶ Heatshrink Moulded Shapes

▶ Mounts

▶ Heavy Duty Mounts

▶ Wire Connectors

▶ Wiring Duct

▶ Wiring Protection

▶ Labels, Printers and Software

▶ Pre-Terminated Networking

▶ Copper Network Solutions

▶ Fiber Network Solutions

▶ Jacks and Wall Plates

▶ Racks - Cable Management

▶ Surface Raceway Systems

156-00551

Cable Tie and Edge Clip, 50lb, Length 200mm, EC9 Panel Thickness 1-3mm, HS Tie, HIRHS Mount, 500/pk

Article Number: 156-00551

Part Number: 156-00551

Type: T50REC9SD

➔ Base Data

Part No.	156-00551
Type	T50REC9SD
Color	Black (BK)
Features	HellermannTyton's cable tie and edge clip assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. The EC9 edge clip features a low profile saddle design at the entry point of the cable tie. This low profile saddle allows for improved tension and a more secure fit around smaller bundle diameters.
Application Method	Cable tie and edge clip assemblies are primarily applied around a bundle by hand and tensioned using one of HellermannTyton's manual or pneumatic hand tools. The bundle is then secured to the mounting surface by inserting the clip onto the appropriate edge.
Identification Plate Position	none
Typical Application	This cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.
Variant	Inside Serrated

➔ Product Dimensions

Min. Tensile Strength	50lbs
Length (L)	7.87" / 200.0mm
Height (H)	0.047" / 1.2mm
Min. Ø Bundle	0.039" / 1.0mm
Max. Ø Bundle	1.77" / 45.0mm
Max. Panel Thickness	0.118" / 3.00mm
Min. Panel Thickness	0.039" / 1.00mm

➔ Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) / Polyamide 6.6 heat stabilized (PA66HS)
Material Specification	RoHS
Min. Extraction Force (N)	225N

➔ Logistic and Packaging

Packaging Type	bag
----------------	-----

➔ Find a Distributor

➔ Order Samples

➔ Get Technical Drawings

Share

http://www.hellermanntyton.us/productDetail.aspx?lon=156-00551&ref=search.aspx[11/11/2013 2:28:38 PM]

Pkg. Qty.	500
Carton Qty.	4000
EAN code	4031026326818
UPC	089306313304

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)