- Cable Ties
- Cable Ties with Fasteners
- Cable Tie Tools
- Clamps and Clips
- Heatshrink Moulded Shapes
- Mounts
- Heavy Duty Mounts
- Wire Connectors
- Wiring Duct
- Wiring Protection
- Labels, Printers and Software
- Pre-Terminated Networking
- Copper Network Solutions
- Fiber Network Solutions
- Jacks and Wall Plates
- Racks - Cable Management
- Surface Raceway Systems

T120S0UVK2

Heavy Duty Cable Tie, 8.9" Long, 120lb Tensile Strength, PA66UV, Black, 50/pkg

Article Number: 111-12860
Part Number: T120S0UVK2
Type: T120S

Find a Distributor
Order Samples
Get Technical Drawings
Share

Base Data

Part No.	T120S0UVK2
Type	T120S
Color	Black (BK)
Features	• UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

Product Dimensions

Min. Tensile Strength	120.0lbs / 535.0N
Length (L)	8.9" / 225.0mm
Width (W) (imperial)	0.3"
Width (W)	7.6mm
Min. Ø Bundle	0.2" / 5.0mm
Max. Ø Bundle	2.2" / 55.0mm
Cable Tie Head Height	7.7mm
Cable Tie Head Length	10mm
Cable Tie Head Width	13.2mm
Thickness	1.6mm

Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
Flammability	UL94 V2
Material Specification	HF / RoHS
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	RoHS

Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

Logistic and Packaging

Packaging Type	pc
Pkg. Qty.	50
Carton Qty.	1500Pieces
EAN code	4031026106519
UPC	089306174394

Find a Distributor | Get Product Samples | Get Technical Drawings

© HellermannTyton North America 2011 | TS16949, ISO 9001 and ISO 14001 Certified
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512