

T120S0PPH4

Heavy Duty Cable Tie, 8.9" Long, 120lb Tensile Strength, PP, Black, 500/pkg

Article Number: 111-12827

Part Number: T120S0PPH4

Type: T120S

➔ **Base Data**

Part No.	T120S0PPH4
Type	T120S
Color	Black (BK)
Features	• Polypropylene cable ties provide excellent resistance to chemicals and salts. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

➔ Product Dimensions

Min. Tensile Strength	60.0lbs / 267.0N
Length (L)	8.9" / 225.0mm
Width (W) (imperial)	0.3"
Width (W)	7.6mm
Min. Ø Bundle	0.2" / 5.0mm
Max. Ø Bundle	2.2" / 55.0mm
Thickness	1.6mm

➔ Material and Specifications

Material	Polypropylene (PP)
Flammability	UL94 HB
Material Specification	RoHS / HF
Operating Temperature	-40 °F to +239 °F (-40 °C to +115 °C)
ROHS Conformity	
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

→ Find a Distributor

➔Order Samples

➔Get Technical Drawings



 Logistic and Packaging

Packaging Type	bag
Pkg. Qty.	500
Carton Qty.	1000
EAN code	4031026312026
UPC	089306061700

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)

[Home](#) | [About HellermannTyton](#) | [Products](#) | [Careers](#) | [Contact](#) | [Terms](#)

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001 Certified](#)
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512