

181-32016

Slotted Wall Wiring Duct, 3" X 2", Non-Adhesive, PVC, Black, 30ft/Box

Article Number: 181-32016

Part Number: 181-32016

Type: SL3X2

[Find a Distributor](#)

[Order Samples](#)

[Get Technical Drawings](#)

[!\[\]\(3342c215b2a8b663596a81468d5dc314\_img.jpg\)](#) [!\[\]\(5e22d44aef1f9548ca8274cbfb388e9d\_img.jpg\)](#) [!\[\]\(b011182daf5a0527ed818f91dc4cf8f7\_img.jpg\)](#) [!\[\]\(e021942709a217cfed2f781c62feb09c\_img.jpg\)](#) | [!\[\]\(189fbc627457efb1015bb006253636f9\_img.jpg\) Share](#)

[Base Data](#)

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part No. | 181-32016                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Type     | SL3X2                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Color    | Black (BK)                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Features | <ul style="list-style-type: none"><li>• Strong fingers prevent unwanted breaking.</li><li>• Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li><li>• Restricted opening design in the finger of the duct helps keep wires in place.</li><li>• Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection</li></ul> |

[Product Dimensions](#)

|                       |                 |
|-----------------------|-----------------|
| Length (L)            | 6.0ft / 1.83m   |
| Width (W) (Imperial)  | 3.03"           |
| Width (W)             | 76.96mm         |
| Width (W2)            | 3.0" / 76.2mm   |
| Width (W3)            | 0.4" / 10.16mm  |
| Width (W4)            | 1.0" / 25.4mm   |
| Width (W5)            | 1.62" / 41.1mm  |
| Width (W6)            | 1.0" / 25.4mm   |
| Height (H)            | 2.0" / 50.8mm   |
| Mounting Hole Centers | 4.00" / 101.6mm |

[Material and Specifications](#)

|                               |                         |
|-------------------------------|-------------------------|
| Material                      | Polyvinylchloride (PVC) |
| Flammability                  | self-extinguishing      |
| Material Specification        | RoHS                    |
| Operating Temperature         | +122 °F (+50 °C)        |
| Specification                 | CSA / UL                |
| UL Recognized (US and Canada) | Yes                     |

[Logistic and Packaging](#)

|                |              |
|----------------|--------------|
| Packaging Type | box          |
| Pkg. Qty.      | 30ft / 9.14m |
| Carton Qty.    | 120          |

|     |              |
|-----|--------------|
| UPC | 089306313014 |
|-----|--------------|

Find a Distributor

Get Product Samples

Get Technical Drawings