

181-44019

Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, Black, 30ft/Box

Article Number: 181-44019

Part Number: 181-44019

Type: SL4X4

[Find a Distributor](#)

[Order Samples](#)

[Get Technical Drawings](#)

[!\[\]\(3342c215b2a8b663596a81468d5dc314\_img.jpg\)](#) [!\[\]\(5e22d44aef1f9548ca8274cbfb388e9d\_img.jpg\)](#) [!\[\]\(b011182daf5a0527ed818f91dc4cf8f7\_img.jpg\)](#) [!\[\]\(e021942709a217cfed2f781c62feb09c\_img.jpg\)](#) | [!\[\]\(189fbc627457efb1015bb006253636f9\_img.jpg\) Share](#)

 Base Data

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part No. | 181-44019                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Type     | SL4X4                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Color    | Black (BK)                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Features | <ul style="list-style-type: none"><li>• Strong fingers prevent unwanted breaking.</li><li>• Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li><li>• Restricted opening design in the finger of the duct helps keep wires in place.</li><li>• Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.</li></ul> |

 Product Dimensions

|                       |                 |
|-----------------------|-----------------|
| Length (L)            | 6.0ft / 1.83m   |
| Width (W) (imperial)  | 4.0"            |
| Width (W)             | 101.6mm         |
| Width (W2)            | 4.0" / 10.6mm   |
| Width (W3)            | 0.4" / 10.16mm  |
| Width (W4)            | 1.0" / 25.4mm   |
| Width (W5)            | 3.6" / 91.4mm   |
| Width (W6)            | 1.5" / 38.1mm   |
| Height (H)            | 4.0" / 101.6mm  |
| Mounting Hole Centers | 4.00" / 101.6mm |

 Material and Specifications

|                               |                         |
|-------------------------------|-------------------------|
| Material                      | Polyvinylchloride (PVC) |
| CSA Certified                 | Yes                     |
| Flammability                  | self-extinguishing      |
| Material Specification        | RoHS                    |
| Operating Temperature         | +122 °F (+50 °C)        |
| Specification                 | UL / CSA                |
| UL Listed (US and Canada)     | No                      |
| UL Recognized (US and Canada) | Yes / Yes               |

 Logistic and Packaging

|                |              |
|----------------|--------------|
| Packaging Type | box          |
| Pkg. Qty.      | 30 / 9.14m   |
| Carton Qty.    | 120          |
| UPC            | 089306295679 |

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)