






# SFH CONNECTOR

1.8 mm pitch/Wire-to-Board connectors/Crimp style and Mating style




This low profile type connector with height of 3.0mm is designed for connection to stroboscope flash and realized space saving.

- Contact lance
- Countermeasure for inverse insertion and locking feature



- Note: 1. The above figure is the figure viewed from the connector mounting side.  
 2. Tolerances are non-cumulative:  $\pm 0.05\text{mm}$  for all centers.  
 3. The dimensions above should serve as a guideline. Contact JST for details.

## Contact



Model No.	Applicable wire			Q'ty/ reel
	mm <sup>2</sup>	AWG#	Insulation O.D. (mm)	
SSFH-001T-P0.5	0.13 to 0.33	26 to 22	0.95 to 1.3	15,000
SSFH-002T-P0.5	0.05 to 0.13	30 to 26	0.7 to 1.25	15,000

### Material and Finish

Copper alloy, tin-plated (reflow treatment)


### RoHS compliance

Contact	Crimping machine	Applicator		
		Crimp applicator	Dies	Crimp applicator with dies
SSFH-001T-P0.5	AP-K2N	MKS-L	MK/SSFH-001-05	APLMK SSFH001-05
		-	-	-
SSFH-002T-P0.5	AP-K2N	MKS-L	MK/SSFH-002-05	APLMK SSFH002-05
		-	-	-

Note: Contact JST for fully automatic crimping applicator.

# SFH CONNECTOR

## Housing




No. of circuits	Model No.	Q'ty/bag
2	SFHR-02V-R	1,000

### Material and Finish

Thermoplastic resin, UL94V-0

RoHS compliance

## Header



No. of circuits	Model No.	Q'ty/reel
2	SM02B-SFHRS-TF	2,000

### Material and Finish

Press pin: Copper alloy, copper-undercoated, tin-plated (reflow treatment)  
Wafer: Heat resisting resin, UL94V-0  
Solder tab: Copper alloy, copper-undercoated, tin-plated (reflow treatment)

RoHS compliance This product displays (LF)(SN) on a label.

## Model number allocation

### Contact

**S SFH- 001 T - P 0.5**

Form: S···Strip form

Series name

Applicable wire range: 001···AWG #26 to #22  
002···AWG #30 to #26

Surface finish: T···Tin-platead (reflow treatment)

Material: P···Copper alloy

Terminal size

### Housing

**SFH R - 02 V - R**

Series name

Part name: Receptacle

No. of circuits: 2

Flammability: V···UL94V-0

Color: R···Red, L···Lemon yellow

### Header

**SM 02 B - SFH R S - TF**

Shape of assembled product:  
SM···SMT side entry style

No. of circuits: 2

Part name: Header

Series name

Color: R···Red, L···Lemon yellow

Clinched (Kinked) / Not clinched: S···Straight

Packaging style: TF···Embossed-taping