

FUSE CLIPS

Underwriters Laboratories, Inc. Recognized Component Program — UL File Number E354010

UL file number E354010 has been assigned to Keystone Electronics' fuse clips with end stops. (Refer to pages 44-45) Indicating recognition by Underwriters Laboratories Inc. that they are in compliance with their component program.

- Available for 5mm, 1AG, 2AG, 3AG, 5AG, 7AG & 8AG sizes
- Low profile, space saving
- Low contact resistance
- Withstands shock and vibration
- Rated 6.3 to 30 Amps
- Custom designs and modifications available to your specifications

Refer to pages 46-47 for Fuse Clip Layout and Mounting Details


PC THRU MOUNT TYPES

- Snap-fit design enhances assembly and PC retention for wave soldering
- Available with orientation legs to assure proper PC installation
- Available with or without end stops

SURFACE MOUNT & RIVET TYPES

- Available with solder lugs or quick-fit tabs .187 (4.7), .205 (5.2)

5mm PC Clips



MATERIAL:


.020 (.51) Brass, Tin Plate

Current Rating: 15 Amps

CAT. NO.	A	B
3517	.060 (1.5)	.060 (1.5)
3518P	.060 (1.5)	.093 (2.4)

With or Without Orientation Legs

Optional cover available - Cat. No. 3517C



- With snap-in PC legs

MATERIAL:


.020 (.51) Brass, Tin Plate

Current Rating: 15 Amps

CAT. NO.	A	B
3512	.060 (1.5)	.060 (1.5)
3512P	.060 (1.5)	.093 (2.4)

With or Without Orientation Legs

Optional cover available - Cat. No. 3517C




MATERIAL:

.016 (.41) Brass, Tin Plate

Current Rating: 6.3 Amps

CAT. NO. 3520




MATERIAL:


.016 (.41) Brass, Tin Plate

Current Rating: 15 Amps

CAT. NO. 3519



Mounting Detail




2AG or 5mm




MATERIAL: .016 (.41) Brass, Tin Plate

Current Rating: 15 Amps

CAT. NO.	PC LEGS	END STOP
3521	YES	YES
3621	YES	NO*
3561	NO	YES
3622	NO	NO*



Mounting Detail
Cat. No. 3521 &
3621 Only



5mm/3AG




MATERIAL:


.016 (.41) Brass, Tin Plate

Current Rating: 15 Amps


CAT. NO. 3562



Mounting Detail



4AG (9/32 Dia.)




MATERIAL:

.020 (.51) Brass, Nickel Plate

Current Rating: 15 Amps

CAT. NO. 3565 (Without End Stops)*



5AG (13/32 Dia.) - Solar Protection Fuse




MATERIAL:


.030 (.76) Brass, Tin Plate

Current Rating: 30 Amps

CAT. NO. 3566



Mounting Detail



*Fuse clips without end stops are not UL recognized