

Part Number 

EGG.1B.302.CLL

Status Active

Size/Series 1B / B

Matching FGG.1B.302.CLAD42

[Request a quote](#)

#### MECHANICAL DETAILS

**Shell Style/Model** EG\*: Fixed receptacle, nut fixing

**Keying** 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

**Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

**Cable Fixing** : 0 - 0 mm

**Variant** :

|     | A    | B    | E    | L    | M    | N    | S1   | S3   | e       |
|-----|------|------|------|------|------|------|------|------|---------|
| mm. | 14   | 16   | 7.5  | 23   | 1.5  | 21.1 | 10.5 | 14   | M12x1.0 |
| in. | 0.55 | 0.63 | 0.30 | 0.91 | 0.06 | 0.83 | 0.41 | 0.55 |         |

#### PERFORMANCE DETAILS

**Insert Configuration** 1B.302 : 2 Low Voltage

**Insulator** L: PEEK

**Specifications**

**Contact Type:** Solder

**Max. Matings:** 5000

**Contact Dia.:** 1.3 mm (0.051in)

**Bucket Dia.:** 1 mm (0.039in)

**Max. Solid Conductor:** 0.5 mm<sup>2</sup> (AWG 20)

**Max. Stranded Conductor:** 0.5 mm<sup>2</sup> (AWG 20)

**R (max):** 3.6 mOhm

**Vtest (contact-shell):** 1350 V (AC), 1910 V (DC)

**Vtest (contact-contact):** 1500 V (AC), 2120 V (DC)

**Rated Current:** 15 A (AC/DC)

#### OTHER CHARACTERISTICS

**Endurance (Shell)**

**Humidity (max):** <=95% [at 60 deg C /140 F]

**Vibration:** 15 g [10 Hz - 2000 Hz]

**Shock Resistance:** 100 g [ 6 ms]

**Salt Spray Corrosion:** >144 hr

**Climatical Category:** 50/175/21

**Shielding (min):** 75 dB (10 MHz)


**Shielding (min):** 40 dB (1 GHz)

**IP Rating** 50

**Catalog**



 [Download 3D draw](#)



"";"";""; Note: You can still get the CAD file even if no 3D preview is displayed below.

The 3D viewer requires the Java Runtime Environment (JRE) and for Java to be enabled on your system.

If Java is not installed, go to <http://www.java.com/en/download/manual.jsp>

For the Firefox users, Java can be blocked by your browser. More info on : <https://addons.mozilla.org/en-US/firefox/blocked/p80>