


EGG.0B.303.CYM
Status Active

Size/Series 0B / B

Matching FGG.0B.303.CYCD25

[Request a quote](#)
MECHANICAL DETAILS

Shell Style/Model	EG*: Fixed receptacle, nut fixing								
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)								
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces								
Cable Fixing	: 0 - 0 mm								
Variant	:								


	A	B	E	L	M	N	S1	S3	e
mm.	10	12.5	7	20.7	1.2	19.1	8.2	11	M9x0.6
in.	0.39	0.49	0.28	0.81	0.05	0.75	0.32	0.43	

PERFORMANCE DETAILS

Insert Configuration	0B.303 : 3 Low Voltage
Insulator	Y: PEEK for crimp contacts
Specifications	
Contact Type:	Crimp
Max. Matings:	5000
Contact Retention:	30 N
Contact Dia.:	0.9 mm (0.035in)
Bucket Dia.:	1.1 mm (0.043in)
Min. Conductor:	0.25 mm ² (AWG 24)
Max. Conductor:	0.5 mm ² (AWG 20)
R (max):	4.8 mOhm
Rated Current:	8 A (AC/DC)
Vtest (contact-shell):	900 V (AC), 1270 V (DC)
Vtest (contact-contact):	1200 V (AC), 1700 V (DC)

OTHER CHARACTERISTICS

Endurance (Shell)	5000
Temp (min)	-55°C deg
Temp (max)	+250°C deg
Humidity (max):	<=95% [at 60 deg C /140 F]
Vibration:	15 g [10 Hz - 2000 Hz]
Shock Resistance:	100 g [6 ms]
Salt Spray Corrosion:	>144 hr
Climatical Category:	50/175/21
Shielding (min):	75 dB (10 MHz)
Shielding (min):	40 dB (1 GHz)
IP Rating	50
Catalog	


[Download 3D draw](#)


"";";";"; Note: You can still get the CAD file even if no 3D preview is displayed below.

The 3D viewer requires the Java Runtime Environment (JRE) and for Java to be enabled on your system.

If Java is not installed, go to

<http://www.java.com/en/download/manual.jsp>

For the Firefox users, Java can be blocked by your browser. More info on :

<https://addons.mozilla.org/en-US/firefox/blocked/p80>