

Part Number . . . [→](#)

PHG.4B.026.CLLD10

Status Active

Size/Series 4B / B

Matching FGG.4B.026.CLAD10

[Request a quote](#)

MECHANICAL DETAILS

- Shell Style/Model** PH*: Free receptacle, cable clamp
- Keying** 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
- Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
- Cable Fixing** D10: 9.1 - 10.5 mm
- Variant** :

	A	L	S1	S2
mm.	26.0	73	21	20
in.	1.02	2.87	0.83	0.79

PERFORMANCE DETAILS

- Insert Configuration** 4B.026 : 2 Fluidic, 12 Low Voltage
- Insulator** L: PEEK

OTHER CHARACTERISTICS

- Endurance (Shell)**
- Humidity (max):** <=95% [at 60 deg C /140 F]
- Vibration:** 15 g [10 Hz - 2000 Hz]
- Shock Resistance:** 100 g [6 ms]
- Salt Spray Corrosion:** >144 hr
- Climatical Category:** 50/175/21
- Shielding (min):** 75 dB (10 MHz)
- Shielding (min):** 40 dB (1 GHz)
- IP Rating** 50
- Catalog**

