


Part Number     [→](#)
**PHG.4K.026.CLLC10**

Status Active

Size/Series 4K / K

[Request a quote](#)
**MECHANICAL DETAILS**

- Shell Style/Model** PH\*: Free receptacle, cable collet
- Keying** 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
- Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
- Cable Fixing** C10: 9.6 - 10.5 mm
- Variant** :

|     | A    | L    | S2   |
|-----|------|------|------|
| mm. | 29   | 75.5 | 19   |
| in. | 1.14 | 2.97 | 0.75 |

**PERFORMANCE DETAILS**

- Insert Configuration** 4K.026 : 2 Fluidic, 12 Low Voltage
- Insulator** L: PEEK

**OTHER CHARACTERISTICS**

- Endurance (Shell)**
- Humidity (max):** <=95% [at 60 deg C /140 F]
- Vibration:** 15 g [10 Hz - 2000 Hz]
- Shock Resistance:** 100 g [ 6 ms]
- Salt Spray Corrosion:** >144 hr
- Climatical Category:** 50/175/21
- Shielding (min):** 95 dB (10 MHz)
- Shielding (min):** 80 dB (1 GHz)
- IP Rating** 68
- Catalog**

